


# General Purpose Shrink Tunnel

Model:

# PP1808-28

can be used with a wide variety of applications



Falcon Belting



Teflon Mesh Belting



Stainless Steel Metal  
Mesh Belting



High Density Rollers - Close  
Roller Spacing 1/2" Gap

The **PP1808-28 Shrink Tunnel** is a great general purpose shrink tunnel that can be used for a wide variety of applications. Can be used with shrink bands, neck bands, full body sleeves, used with shrink film, used as a drying or curing tunnel etc.

## Standard Features of Shrink Tunnel Include:

- Fully Re-Circulating Air Chamber
- Live Roller Rod Conveyor
- Digital Temperature Control 0-400°
- Adjustable Air Velocity Control
- State-of-the-Art AC Variable Speed Drive 0-75 FPM
- Chromed Conveyor Rollers and Shaft (No Rust)
- Automatic Tunnel Cool Down with Shut Off
- 1/2 HP Blower Motor
- Sealed Bearings on Drive and Idler Shafts
- Chamber Size 18"W x 8"H x 28"L
- Quietest Tunnel on the Market
- Heats up to 300° F in less than 15 minutes
- Thermal Overload Protection on All Motors
- Locking Casters with Leveling Screws
- Anti-Jam Safety Features on Conveyor
- 7.5 KW Heater Bank
- 2 year warranty

*\*Optional Tunnel Height of 12" Opening also Available.*

## Preferred Pack®

The New Industry Standard for Quality and Reliability

Line of Equipment by **EXCEL** PACKAGING

**General Purpose Shrink Tunnel**



**Specifications:**

| MODEL     | VOLTS | POWER |      | WEIGHT | TUNNEL OPENING |    |    | SPEED    |
|-----------|-------|-------|------|--------|----------------|----|----|----------|
|           |       | PHASE | AMPS |        | L              | W  | H  |          |
| PP1808-28 | 220   | 1     | 40   | 450    | 28             | 18 | 8  | 0-75 FPM |
| PP1812-28 | 220   | 1     | 40   | 470    | 28             | 18 | 12 | 0-75 FPM |

**Available Options:**

- 12" Tunnel Opening
- Close Roller Spacing 1/2" Gap
- Teflon Mesh Belt
- Stainless Steel Metal Mesh Belt

